Appln. No.: to be assigned

Preliminary Amendment Dated April 21, 2005

<u>Amendments to the Claims:</u> This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- 1. (Currently Amended) A method of processing metal parts and the like by blanking, the method comprising the steps of: performing a first blanking step on a semi-finished product (1) in order to produce a blanked semi-finished product (20), and of performing a subsequent processing of the blanked semi-finished product to produce a final product (30, 40), characterized in that wherein the first blanking step is performed leaving an allowance on the blanked semi-finished product (20), and in that the subsequent processing comprises at least one second blanking step by which the allowance is removed from the blanked semi-finished product.
- 2. (Currently Amended) A The method according to Claim claim 1 in which the allowance has a thickness of between 0.1 and 1.0 mm.
- 3. (Currently Amended) A-The method according to Claim-claim 2 in which the allowance has a thickness of between 0.20 and 0.25 mm.
- 4. (Currently Amended) A-<u>The</u> method according to one or more of the preceding claims <u>1</u> in which the subsequent processing comprises a tumbling step after the second blanking step.
- 5. (Currently Amended) A-The method according to one or more of the preceding claims 1 comprising, prior to the first blanking step, the step of coining of the semi-finished product (1) to produce a coined semi-finished product-(10).
- 6. (Currently Amended) A-The method according to Claim 5 in which the coined semi-finished product comprises at least a first pair of locating appendages (4a) for locating the coined semi-finished product on a die in order to perform the first blanking step.
- 7. (Currently Amended) A-The method according to Claim-claim 6 in which the coined semi-finished product comprises a second pair of locating appendages—(4b), the first pair being removed during the first blanking step and the second pair being removed during the second blanking step.
- 8. (Currently Amended) A method according to Claim-claim 7 in which the second pair of locating appendages (4b) is positioned on surfaces of the semi-finished product which are to be processed further after the second blanking step and/or which are not in view upon completion of the processing.

Appln. No.: to be assigned

Preliminary Amendment Dated April 21, 2005

9. (Currently Amended) A-The method according to one or more of the preceding claims 1 in which the final product (30, 40) is a portion of a spectacle frame.

10. (Currently Amended) A-<u>The</u> method according to one or more of the preceding claims 1 in which the metal of the semi-finished product is selected from brass, nickel silver, and aluminium.